



MICRODYNE™

Live Bacteria Waste Digester



FEATURES

- Stabilized bacterial base
- Immediate deodorizing action
- Digests organic waste

BENEFITS

- Exceptional shelf life
- Problems solved quickly
- Keeps drains flowing freely

RECOMMENDED USES

Bacterial digestion of waste matter in drain lines, grease traps, septic tanks, portable toilets, RVs and boats, and odor control in restrooms, dumpsters and pet areas.

SPECIFICATIONS

Color : Light purple
Scent/Odor: Floral
Character : Opaque, non-viscous liquid
Foam : Low

pH use dilution : 6.0 - 8.0
Phosphorus content : 0.0%
Approvals : cRc



IMPORTANT

Read and understand the label and Safety Data Sheet (SDS). These provide a description of hazards, precautions, personal protective equipment, first aid, 24 Hour Emergency lines, storage data and other safe handling information. The SDS is available on our website at www.uschemical.com and is also available by scanning the QR code on the label.

PRODUCT DIRECTIONS

EQUIPMENT TO USE

Trigger sprayer, appropriate measuring device.

DIRECTIONS TO USE

Treat systems at night or during lowest use period. Avoid the use of bleach, hot water, disinfectants or other harsh chemicals soon after application. These materials will destroy the bacteria cultures before they have time to work. **ODOR CONTROL**: For restrooms, kitchens & hard surfaces dilute 1:1 with warm tap water. Spray directly into and around odor causing materials and surfaces such as urinals, toilets, porous wall and floor grouting, garbage cans, dumpsters, etc. Allow Microdyne to soak into porous surfaces. Heavily soiled surfaces should be pre-cleaned and rinsed before using. (Use a neutral cleaner.) For carpets, rugs, upholstery dilute 1:1 with warm water. **SPOT TREATMENT**: Spray directly on to and around spot. Use liberally so that carpet fibers and backing are completely treated. Brush area. Place a clean towel, moistened with diluted product over treated area. Keep moist for 24 hrs. Repeat if necessary. **PRE-CLEAN TREATMENT**: Spray diluted solution over stained or odor causing areas. Follow with extraction or shampoo. **DRAIN LINES**: Add 3 oz. twice a week. Start at lowest floor and proceed upwards on daily intervals until each floor is treated. Treat other points of waste entry such as toilet bowls, urinals, pot sinks, garbage disposals and dishwasher scrapper drain weekly. Add 2 oz. to each. **RVs & BOATS**: Add 2 oz. per gallon in holding tank. **PUMP STATIONS**: Add 1 oz. per 50 gallons of tank capacity. **PORTA TOILETS**: Add two quarts directly and add sufficient water to cover solids.

PACKAGING

This product is available in 12/1 quart cases (065371) and 4/1 gallon cases (5011518).



L003622

Copyright© 2021 U S Chemical, Watertown WI 53094
www.uschemical.com

07/21

O D O R C O N T R O L